PRODUCT SHEET



TECHNICALL

Lighting specs.
Luminous flux 100%: 2400LM
Luminous Flux 20%: 500Lm
Power light 100%: 30Watt
Power light 20%: 7Watt
Light color (CCT) options: 3000K OR
4000K
color:> 80

- Supply voltage: 230V AC
- Motion Sensor (PIR) Mounting: Luminaire front Detection angle: 3600 Detection height: 5 m Delay time: 1 minute
- Emergency Minimum running time: 3 hours Battery Type: Ni-MH Capacity: 2000mAh Charging time (fast): 2.3uur Power charger included: 3Watt
- Article number: RK-3030

DURABLE AND MAINTENANCE FREE

RUKRA LED ARMATURE

sensor

Sensor

The RUKRA LED Armature is equipped with its own back-up battery and is very energy efficient. Especially in elevator cabin's where the light is on 24 hours a day directly energy saving is realized. You save energy because the LED dims when nobody is present in the elevator car.

Once someone enters the elevator cabin the built-in motion sensor will detect this immediately and maintain illumination at normal strength.

LED lighting live much longer, at least 80,000 hours or up to 10 years! Significant cost savings in lighting energy, maintenance and replacement and ensure that your investment is often recouped within two years.

INCLUDING EMERGENCY LIGHT

RUKRA EUROPE B.V.

WWW.RUKRA.EU